

PUMPS

DUAL PURPOSE PUMPS

- Operates submersed or in-line (water-fed via pipe/hose)
- Cast aluminum housing with protective epoxy coating
- Threaded intake and discharge
- Nylon pumping head and impeller
- Thermal overload protection
- For use with water only
- 10' power cord
- Nylon screen
- UL listed, CSA certified

Little GIANT
PUMP COMPANY

Model No. DA328

- 3/8" FNPT intake and 1/4" MNPT discharge
- Buna-N seal
- 1.7 amps
- 100 watts
- 5 1/2" L x 3 1/2" W x 4 3/4" H

Model No. DA329

- 1/2" FNPT intake and 1/2" MNPT discharge
- Viton® Seal
- 3.2 amps
- 200 watts
- 7" L x 4 1/2" W x 5 1/2" H



AUTOMATIC CONDENSATE REMOVAL PUMPS - VCMA SERIES

- Vertical type pump unit
- 1/2 gallon leak proof, rustproof, ABS tank with mounting tabs
- Stainless steel motor shaft
- Three drain holes
- 3/8" O.D. barbed discharge adapter and removable 3/8" barbed check valve
- Snap-action safety switch
- Thermal overload protected
- Suitable for high-efficiency, gas furnace condensate
- 15' shut-off head
- 6' power cord
- Weight: 4.40 lbs.
- UL/CSA listed



Construction

Motor: 1/50 HP high performance

Intermittent liquid temperature: Up to 120°F

Discharge: 3/8" OD barbed

Housing: ABS

Cover: ABS

Volute: ABS

Impeller: Glass filled polypropylene

Model No. DC294

Price/Each \$

Little GIANT
PUMP COMPANY

Model No.	HP	Volts	Gallons/Hour			Shut Off'	PSI	Wt. lbs.	Price /Each
			1'	3'	5'				
DA328	1/40	115	300	255	205	70	11.8	5.1	4
DA329	1/15	115	500	435	337	210	17.3	7.5	8

NON-SUBMERSIBLE, SELF-PRIMING PLATED BRASS TRANSFER PUMPS

- 1/10 HP, 115 V, 60 Hz, 1.6 Amps motor
- 360 GPH @ 1"
- Self-priming for instant delivery or de-watering up to 6'
- Non-submersible plated brass pump body
- Rugged metallic handle for easy portability
- Dual threaded intake and discharge with both 3/4" male garden hose thread and 3/8" FNPT
- Includes: pump, hose, strainer and suction adapter

Model No. DC293

Price/Each \$

PUMP ONLY

Model No. DC196

Price/Each \$



Little GIANT
PUMP COMPANY

CONTRAFLEX WATER DISCHARGE HOSES

- Extremely durable hose
- Layflat design for easy handling
- 25' and 50' lengths with C and E cam and groove fittings assembled



Model No.	Size	Price /Each
TEB656	1.5" x 25'	
TEB651	1.5" x 50'	
TEB657	2" x 25'	
TEB652	2" x 50'	
TEB658	2.5" x 25'	

Model No.	Size	Price /Each
TEB653	2.5" x 50'	
TEB659	3" x 25'	
TEB654	3" x 50'	
TEB660	4" x 25'	
TEB655	4" x 50'	

ALUMINUM CAM & GROOVE FITTINGS

- Simple to use quick connect fittings
- Very reliable and durable



Size"	Part A	Price /Each	Part B	Price /Each	Part C	Price /Each	Part D	Price /Each	Part E	Price /Each	Part F	Price /Each
1	WL016		WL027		WL038		WL049		WL060		WL071	
1 1/4	WL017		WL028		WL039		WL050		WL061		WL072	
1 1/2	WL018		WL029		WL040		WL051		WL062		WL073	
2	WL019		WL030		WL041		WL052		WL063		WL074	
2 1/2	WL020		WL031		WL042		WL053		WL064		WL075	
3	WL021		WL032		WL043		WL054		WL065		WL076	
4	WL022		WL033		WL044		WL055		WL066		WL077	

PVC SUCTION & DISCHARGE HOSES

- Excellent weather and abrasion resistance
- Perfect for construction pumps, trash pumps, mining and quarry use
- 25' lengths with C Cam, Groove fitting and combination nipple fully assembled
- Hoses 1 1/2" and over come with an assembled basket strainer



Model No.	Size"	Price/Each
TEB644	1	
TEB645	1.25	
TEB646	1.5	
TEB647	2	
TEB648	2.5	
TEB649	3	
TEB650	4	